# **UCH**

# UCH Series Coin Hopper

- Wide range of coin size acceptable in single hardware
- High payout speed
- Payout to last coin
- Convenient firmware upgrade via USB flash drive
- Twin connection coin path
- Anti-jamming design
- Power supply for both 12V and 24V
- Easy installation base
- Easy maintenance



# **UCH Series Coin Hopper**

ICT launches new UCH hopper with enhanced reliability and robust design. UCH is equipped with advanced micro processor which is fully compatible with ccTalk AES interface to fulfill market requirement. Single hardware design of UCH hopper can accept wide range of different coin sizes, and also help reduce inventory.

# **Specifications**



#### Interface

ccTalk ccTalk AES Pulse Hopper Red Flag



# Dispensing Speed

Max. 6 coins/second



# **Applicable Coin Size**

Diameter: 20mm – 28mm Thickness: 1.6mm – 3.2mm



## Coin Capacity

ca. 400 coins (1€)



# Coin Quantity Detection

Optical Empty Sensor (2 adjustable positions)

Optical Full Sensor (2 adjustable positions)



## Power Source

12V DC±10% 24V DC±10%



## **Power Consumption**

Standby: ≦ 50mA, 1.2W Operation: ≦ 750mA, 18W Maximum: ≦ 3A, 72W



## Dimension

L154 x W139.2 x H155 mm/ L6.1 x W5.5 x H6.1 inches



#### Weight

Approx. 800g



## Environmental

Operating Temperature: 5°C/41°F~50°C/122°F

Storage Temperature:
-30°C/-22°F~70°C/158°F
Humidity:

30%~85%RH(no condensation)



# **Recommended Applications**

Gaming/Amusement

-Specifications are subject to change without prior notice.









# **International Currency Technologies**

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

EMail: sales@ictgroup.com.tw (Product Information) rma@ictgroup.com.tw (Technical Service) Website: www.ictgroup.com.tw